


**GENERAL DATA**

**Division :** Fall Protection  
**Family :** Fall Protection  
**Range :** Harness  
**Brand formerly known as :** MILLER  
**Business Countries**  
 EMEA  
 United Kingdom  
 Middle East  
**Activity Domains :**  
 Homeland defense • Army - Defence


**Product Use :**

Rope Access and Rescue Harness with standard fixing buckles - Size L/XL. The ROPAX harness is ideal for industrial rope access, rescue and the special forces. It can be used in conjunction with a climber's seat and an ascender (correctly positioned by using the detachable front webbing sling)

**PRODUCT ADVANTAGES**
**Feature :**

3-point full body harness with dorsal D-ring, sternal and ventral anchorage points, 19mm wide comfort waist belt with 2 side D-rings for work positioning and tool loops; front webbing sling for ascender and padded leg straps with clear 'Left' and 'Right' labeling and standard fixing buckles. A new triangular suspension design spreads the pressure across 4 points rather than 2.

**Benefit :**

**Enhanced Ergonomics and Increased User Comfort :** New Triangular Suspension position splits the forces between the leg straps and the waist belt across 4 points of pressure) rather than being concentrated on the legs, thus reducing the risks of suspension trauma.

The V form of the shoulder straps positions the straps away from the neck to avoid any irritation due to the webbing rubbing.

**Maximised Productivity :** A detachable webbing sling on the chest straps positions the ascender correctly in a vertical position to facilitate ascension.

**Ease of Use and Fit :** The leg straps and anchorage points are clearly identified.

**Optimum Abrasion and Chemical Resistance :** The black polyester webbing and stainless steel components offer optimum durability.

**Adaptability :** An attachment for a climber's seat makes the harness suitable for multi-application scenarios.

**Lightweight :** Only 1.6kg

## TECHNICAL DESCRIPTION

### Dorsal D-Ring

**D-Ring Information :**  
BENT BUCKLE

**Raw Material :**  
Aluminium alloy

**Dimensions :**  
60x64x7mm

**Breaking Strength :**  
2300 daN

### Ventral Anchorage point

**Description :**  
RING

**Raw Material :**  
Stainless steel

**Dimensions :**  
Øwire 8mm - Øint 49mm

**Breaking Strength :**  
3000 daN

### Adjustement Buckles

**Raw Material :**  
aluminium alloy

**Breaking Strength :**  
900 daN

### Belt

**Side D-Rings :**  
Aluminium alloy

**Dimensions :**  
60x64x7mm

### Padding

**Material :**  
3D comfort padding in polyester, with knitted mesh

### Performance

**Operating Temperature :**  
-40°C to +80°C

### General Information

**Weight (kg) :**  
1.6kg

**Size :**  
L/XL

**Complementary Information :**  
Screw gate Karabiner  
Opening 24mm  
Raw material: Aluminium alloy  
Breaking strength: 3000 daN

## ADDITIONAL INFORMATION

**User manual number :**  
EN361-358

## CERTIFICATION AND CONFORMITY

**European Directives :**  
89/686/EEC

**EC Category PPE\* :** Category III

**Standards :**  
EN358 / EN361 / EN813

**Quality Assurance :**  
ISO 9001 / 2000

**EC Certification Number :**  
333 AFAQ

**EC Attestation Number :**  
0082/490/160/12/05/0422 EXT N°01/08/06

**Laboratory :**  
APAVE Lyonnaise

\*PPE : Personal Protective Equipment

**FEPAKO**  
VISITA NUESTRA TIENDA  
EN **FEPAKO.COM**

## EC CONFORMITY DECLARATION

**The manufacturer or its legal representative supplier settled in the European Community:**

Miller by Sperian

**Declares that the next Personal Protective Equipment described here after is in conformity with the provisions of Council Directive 89/686/CEE:**

Designation: ROPAX Harness

Reference: 1014435

Standard(s): EN358 EN361 EN813

**This PPE is the object of the above EC attestation type:**

0082/490/160/12/05/0422 EXT N°01/08/06

**Delivered by:**

APAVE Lyonnaise

177 route de Saint-Bel

BP 3

69811 TASSIN CEDEX

France

**Made at Vierzon, on the 10/31/2005**

**By: Yves Depin**

**Division: Fall Protection**



FEPAKO  
VISITA NUESTRA TIENDA  
EN FEPAKO.COM