


GENERAL DATA

Division : Fall Protection
Family : Fall Protection
Range : Harness
Brand formerly known as : MILLER
Business Countries
 EMEA
 United Kingdom
 Middle East
Activity Domains :
 Homeland defense • Army - Defence


Product Use :

Rope Access and Rescue Harness with automatic fixing buckles - Size S/M. The ROPAX harness is ideal for industrial rope access, rescue and the special forces. It can be used in conjunction with a climber's seat and an ascender (correctly positioned by using the detachable front webbing sling)

PRODUCT ADVANTAGES
Feature :

3-point full body harness with dorsal D-ring, sternal and ventral anchorage points, 19mm wide comfort waist belt with 2 side D-rings for work positioning and tool loops; front webbing sling for ascender and padded leg straps with clear 'Left' and 'Right' labeling and automatic fixing buckles. A new triangular suspension design spreads the pressure across 4 points rather than 2.

Benefit :

Enhanced Ergonomics and Increased User Comfort : New Triangular Suspension position splits the forces between the leg straps and the waist belt (across 4 points of pressure) rather than being concentrated on the legs, thus reducing the risks of suspension trauma. The V form of the shoulder straps positions the straps away from the neck to avoid any irritation due to the webbing rubbing.

Maximised Productivity : A detachable webbing sling on the chest straps positions the ascender correctly in a vertical position to facilitate ascension.

Ease of Use and Fit : The leg straps and anchorage points are clearly identified. The automatic fixing buckles allow for the harness to be fitted quickly and easily.

Optimum Abrasion and Chemical Resistance : The black polyester webbing and stainless steel components offer optimum durability.

Adaptability : An attachment for a climber's seat makes the harness suitable for multi-application scenarios.

Lightweight : Only 1.6kg

TECHNICAL DESCRIPTION

Dorsal D-Ring

D-Ring Information :
BENT BUCKLE

Raw Material :
Aluminium alloy

Dimensions :
60x64x7mm

Breaking Strength :
2300 daN

Front D-Rings

Raw Material :
Aluminium alloy

Breaking Strength :
2300 daN

Ventral Anchorage point

Description :
RING

Raw Material :
Stainless Steel

Dimensions :
Øwire 8mm - Øint 49mm

Breaking Strength :
3000 daN

Adjustement Buckles

Raw Material :
aluminium alloy

Breaking Strength :
900 daN

Belt

Side D-Rings :
Aluminium alloy

Dimensions :
60x64x7mm

Padding

Material :
3D comfort padding in polyester, with knitted mesh

General Information

Weight (kg) :
1,6 Kg

Size :
S/M

Complementary Information :
Screw gate Karabiner
Opening 24mm
Raw material: Aluminium alloy
Breaking strength: 3000 daN

FEPAKO
VISITA NUESTRA TIENDA
EN FEPAKO.COM

ADDITIONAL INFORMATION

User manual number :
EN361-358

CERTIFICATION AND CONFORMITY

European Directives :
89/686/EEC

EC Category PPE* : Category III

Standards :
EN358 / EN361 / EN813

Quality Assurance :
ISO 9001 / 2000

EC Certification Number :
333 AFAQ

EC Attestation Number :
0082/490/160/12/05/0421 EXT N°01/08/06

Laboratory :
APAVE Lyonnaise

*PPE : Personal Protective Equipment

FEPAKO
VISITA NUESTRA TIENDA
EN FEPAKO.COM

EC CONFORMITY DECLARATION

The manufacturer or its legal representative supplier settled in the European Community:

Miller by Sperian

Declares that the next Personal Protective Equipment described here after is in conformity with the provisions of Council Directive 89/686/CEE:

Designation: ROPAX Harness

Reference: 1014432

Standard(s): EN358 EN361 EN813

This PPE is the object of the above EC attestation type:

0082/490/160/12/05/0421 EXT N°01/08/06

Delivered by:

APAVE Lyonnaise

177 route de Saint-Bel

BP 3

69811 TASSIN CEDEX

France

Made at Vierzon, on the 10/31/2005

By: Yves Depin

Division: Fall Protection



FEPAKO
VISITA NUESTRA TIENDA
EN FEPAKO.COM