



PRODUCT NUMBER: 1033537
Miller H-Design® BodyFit auto
2LO Size 2

Miller H-Design® BodyFit harness with 2 sternal webbing loops and automatic buckles on chest and legs straps and DuraFlex stretch webbing. Size 2.



Visítanos en www.fepako.com

Overview

Reference Number

1033537

Product Type

Fall Protection

Range

Harness

Brand

Miller by Honeywell

Industry

- Maintenance
- Utilities

Product Use

The Miller H-Design® BodyFit full body harness dedicated to Electricity, telecommunications and general industry (maintenance...) sectors providing more comfort, freedom of movements and safety to workers thanks to its patented vertically adjustable belt and Breathable padding.

Features & Benefits

Feature

Shoulder Straps : Duraflex Stretch 44,5 mm webbing PES with PTFE treatment (water repellent / anti stain) Colour : green with a black drawing Breaking strength : > 2200 daN

Feature

Other Straps : Standard black webbing 44 mm PES with PTFE treatment (water repellent / anti stain) Breaking strength :> 2700 daN

Feature

Back Anchorage D-ring : Material : steel Finish : Zinc plated Silver Breaking strength : > 2300 daN

Feature

Sternal anchorage point : 2 large textil loops

Feature

Automatic buckles in aluminium Breaking strength: > 900 daN

Feature

Steel mating buckles : Finish : Zinc plated Silver Breaking strength :> 900 daN

Feature

Work positioning belt : Standard green 44 mm webbing: Polyester with PTFE treatment (water repellent / anti stain)
Breaking strength: > 2700 daN Side D rings in Zinc plated & Breaking strength: > 15 KN

Feature

Tool holders : 4 metallic buckles resist at 500 daN 1 textile loop resists at 1200 daN

Feature

Weight : 1,72 Kgs. Breaking strength:> 15 KN Temperature: -30°C to +50°C EN 361 & EN 358

Feature

Certified for a maximum load of 140 kgs.

Benefit

COMFORT AND FREEDOM OF MOVEMENTS o Exclusive H architecture of the harness, thanks to its ergonomically placed webbing, providing a total freedom of movements for the arms. o Horizontal leg straps preventing uncomfortable friction on the legs and on the groin (vs traditional leg straps) increasing comfort for the user during work. o Stretch webbing on the shoulders to provide even more comfort. o Belt with ergonomic and breathable padding for greater comfort at work

Benefit

EASY AND QUICK ADJUSTABILITY & CONNECTION o Easy to access and adjust buckles: intuitive movement up to down. o Very accessible anchor points: bended position back D-ring o Adjustable chest strap for a perfect fit in height and width. o Adjustable leg straps. o Easy Front strap clip. o Long front loops for easy connection. o Belt provided with large lateral D rings, for easy connection for work positioning. o Rotating and unique vertically adjustable belt patented)

Benefit

GREATER SAFETY AND EASIER TRACEABILITY: o Fluo green textile, high visible stitching, front and back fall indicators to facilitate visual inspection before working. o Labels improving yearly checking follow-up for a better traceability o Water-repellent and stain free webbing for greater product durability.

Certifications

 E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Attestation

 1033536 to 1033538 CE certificate

EC Attestation Number

0082/490/160/01/15/0017

Certifications

- EN 361
- EN 358

Additional Information

User Manual

NT90024118 IND D

Maintenance

Life Cycle

Life expectancy of our harnesses is 10 years from the date of manufacture.

Storage Information

Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Care Instructions

Please remember that:

- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.

fepako
Protección

Packaging

EAN Code

3660681059178

Country of Origin

Europe

Visítanos en www.fepako.com

© Honeywell International Inc.

ATTESTATION D'EXAMEN CE DE TYPE

(EC Type examination certificate)

N° 0082/490/160/01/15/0017

A l'équipement suivant : EPI de catégorie III – Harnais d'antichute, ceinture de maintien au travail
To the following equipment: PPE category III – Full body Harness, Work positioning belt

Marque commerciale : MILLER®
Trademark

Référence : H-D DURAFLEX BODYFIT AUTO 2LO
Reference

La présente attestation est attribuée aux cinq tailles suivantes :
This certificate is awarded to the five following sizes

- **Taille 0** – Très petite taille
Size 0 - Extra small size
- **Taille 1** – Petite taille
Size 1 - Small size
- **Taille 2** – Taille moyenne
Size 2 - Medium size
- **Taille 3** – Grande taille
Size 3 - Large size
- **Taille 4** – Très grande taille
Size 4 - Extra large size

Fabricant : HONEYWELL FALL PROTECTION France SAS – 35-37 rue de la Bidauderie – 18100
Manufacturer VIERZON – France

Description : Harnais d'antichute à deux points d'accrochage antichute (1 frontal et 1 dorsal). Point d'accrochage dorsal par dé métallique référence 90023604. Point d'accrochage frontal par deux boucles en sangle à relier par un connecteur conforme à la Norme Européenne EN362. Ceinture de maintien au travail ajustable à deux points d'accrochage latéraux, symétriques et équivalents par dés métalliques double barre référence 90008225. Fermeture de la bavaroise, de la ceinture et des tours de cuisses par boucles automatiques référence 90011216. Réglage des bretelles par boucles métalliques mâle/femelle référence 90023603 et 90023602. Ce harnais antichute à également été testé à 140kg (description détaillée dans le rapport d'examen CE de type 14.6.0658).

Description: Full body harness including two fall arrest attachment points (1 front and 1 back). Back fall arrest attachment point by metallic D-ring reference 90023604. Front fall arrest attachment point by two webbing buckles to link with connector conforms to the European Standard EN362. Adjustable work positioning belt with two fixe, symmetrical and equivalent attachment points by metallic double D-ring reference 90008225 Front webbing, belt and leg loops adjustment by automatic metallic buckles reference 90011216. Shoulder strap front adjustment by metallic male/female buckles reference 90023603 and 90023602. This full body harness was also tested for 140kg (detailed description in EC type examination report 14.6.0658).

Référentiel technique utilisé : EN 361 : 2002 et EN 358 : 1999
Technical referential in use

Date : 08 janvier 2015
Date: 08th January 2015

Le Responsable du Centre d'Essais et de Certification EPI
Head of PPE Testing and Certification Centre
Immaterial original



Document original immatériel


VINCENT MAILLOCHÉAU

Honeywell

E.C. Declaration of Conformity

The manufacturer or its legal representative supplier in the European Community:
Honeywell Safety Products Europe

Declares that the Personal Protective Equipment described here after conforms to the provisions of the European Council Directive 89/686/CEE:

Designation: Miller H-Design® BodyFit auto 2LO Size 2

Reference: 1033537

Standard(s): EN358, EN361

This PPE is the object of the below EC examination certificate n°:

And is subject to the procedure set out in Article 11 point B of Directive 89/686/EEC under the supervision of the below notified body.

Delivered by:

APAVE SUD EUROPE SAS
8 rue Jean-Jacques Vernazza
ZAC. Saumaty-Séon – BP 193
13322 MARSEILLE Cedex 16
France

Drawn up in , on the 17/03/2018

By: Frédéric Wagner

Division: Fall Protection



ZI Paris Nord II 33, rue des Vanesses BP 50288 95958 Roissy CDG France

Tel: +33 (0) 49 90 79 79 Fax: +33 (0)1 49 90 79 80

www.honeywellsafety.com