

NORTHFLEX CUT-RESISTANT GLOVES

NFD11HD  
COLD GRIP PLUS 5™



PRODUCT DESCRIPTION			
PART #	SIZES	OVEREDGE COLORS	CASE PACK
NFD11HD/7S	7/Small	Black	12 per bag/72 per case
NFD11HD/8M	8/Medium	Black	12 per bag/72 per case
NFD11HD/9L	9/Large	Black	12 per bag/72 per case
NFD11HD/10XL	10/XLarge	Black	12 per bag/72 per case
NFD11HD/11XXL	11/XXLarge	Black	12 per bag/72 per case

GLOVE COMPOSITION			
Shell Material:	Engineered cut-resistant fiber	Material Color:	High visibility orange
Shell Weight/Gauge:	15g outer, brushed thermal liner	Coating Color:	Black
Coating Material:	Foamed polyvinyl chloride (PVC)	Coating Pattern:	¾ Dipped
Country of Origin	Pakistan		

PRODUCT FEATURES

- Unique shell construction with cut-resistant outer and brushed thermal inner liner provides excellent insulation from the cold.
- High-viz orange outer shell enhances worker safety with greater low-light visibility.
- Foamed PVC coating provides excellent abrasion resistance and grip in both wet & dry environments.
- Extended knuckle coating offers greater protection in wet environments and protects the backs of fingers.
- Glove retains flexibility, even at low temperatures.
- Recommended for temperatures down to -15°F (-26°C).


APPLICATIONS

Construction | Mining | Masonry Work | Oil and Gas | Sheet Metal and Glass Handling | Trash Collection and Recycling

# NORTH® HAND PROTECTION – Technical Data Sheet

## CERTIFICATIONS / STANDARDS

**OSHA Standard - 29 CFR 1915.157** The employer shall ensure that each affected employee uses appropriate hand protection and other protective clothing where there is exposure to hazards such as skin absorption of harmful substances, severe cuts or lacerations, severe abrasions, punctures, chemical burns, thermal burns, harmful temperature extremes, and sharp objects.

	TEST METHOD	LEVEL	TEST RESULT
 <b>4 5 4 2      020</b>	EN 388		
	Abrasion	4	≥ 8,000 cycles
	Cut	5	≥ 20 index
	Tear	4	≥ 75 newtons
	Puncture	2	≥ 20 newtons
	EN511	020	
ANSI/ISEA 105	ASTM D3389-05 Abrasion		
	ASTM F1790-97 Cut	4	>1500 grams

## LAUNDERING / STORAGE

Product withstands commercial laundry-room detergents (up to pH 14) and warm water temperatures up to 120°F (49°C). Lower heat settings (up to 180°F) are suggested for drying as extreme heat may cause shrinking and degradation of fiber.

Indefinite shelf life when stored in original packaging in a cool dry place away from light. Recommended temperature range: 50°F to 86°F (10°C to 30°C).



## WARNINGS

- Gloves are cut-resistant, not cut proof. Extreme caution should be used around moving machinery.
- Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause personal injury, serious illness or death.

## LIMITED WARRANTY

Honeywell products are covered by and subject to the terms of the Honeywell Safety Products Limited Warranty that is printed in our published price list. The Honeywell Safety Products Limited Warranty is the only written warranty of any force and effect, and all other written warranties are disclaimed in their entirety. In no event shall Honeywell Safety Products or any of its authorized dealers be liable for any damages in excess of the purchase price of the relevant product. This limitation applies to damages of any kind, including but not limited to direct or indirect damages or other special, incidental, exemplary or consequential damages, whether arising out of the use of, or inability to use the product, even if we or any of our authorized dealers has been advised of the possibility of the damages or any claim by any other party

Honeywell Safety Products  
900 Douglas Pike  
Smithfield, RI 02917  
Tel: 800.430.5490  
Fax: 800.572.6346

CANADA  
Tel: 888.212.7233  
Fax: 888.667.8477

[www.honeywellsafety.com](http://www.honeywellsafety.com)

**Honeywell**